

# High Capacity Drying Rack (JZDRA-115)




## CONSTRUCTION/MATERIAL:

- Sturdy construction specifically designed for the demanding corrections environment
- All welded construction
- All fasteners are tamper-proof
- Type 6063-T5 aluminum alloy with wall thickness of 0.070"

## WARRANTY/MAINTENANCE:

- Aluminum: 5-year warranty against manufacturing defect

## COMPATIBLE INSERTS: JZDRI-3, JZDRI-4



## DIMENSIONS/CAPACITY:

Height 72.63" Width 80.50" Depth 22.88"

### CAPACITY:

#### *5 Rows of 3-Rib Inserts*

PPST-9300 Tray	230
PPST-9400 Tray	230
JZCC-5200 Tray	345
JZCC-420 Tray	345

#### *Top Row with 4-Rib Inserts*

PPST-9300 Tray	184
PPST-9400 Tray	184
JZCC-5200 Tray	276
JZCC-420 Tray	276
JZCC-420 Tray	220

## COMPONENTS:

### Shelving

- Five shelves
- Eight inserts per shelf, 32 inserts per rack
- Interchangeable inserts – mix and match

### Casters

- Four 6" poly swivel casters with brakes

## INSERTS:

- Inserts made of copolymer material
- Dishwasher safe, temps up to 212° F
- Shatterproof and resists sharpening

### JZDRI-3

- 3" slots (for segregated & insulated trays)
- 24 slots per shelf, 48 per rack

### JZDRI-4

- 1.125" slots (for lids & sheet pans)
- 55 slots per shelf, 220 per rack