

# Universal Drying Rack (JZDRA-156)



## CONSTRUCTION/MATERIAL:

- Sturdy construction specifically designed for the demanding corrections environment
- All welded construction
- All fasteners are tamper-proof
- Type 6063-T5 aluminum alloy with wall thickness of 0.070"

## WARRANTY/MAINTENANCE:

- Aluminum: 5-year warranty against manufacturing defect

## COMPATIBLE INSERTS: JZDRI-3, JZDRI-4, JZDRI-5



## DIMENSIONS/CAPACITY:

Height 72.63" Width 80.50" Depth 22.88"

### CAPACITY:

### Rack Capacity Per Insert

Item to Dry	JZDRI-3	JZDRI-4	JZDRI-5
Sm & Med Seg Trays	276		
Sm & Med Seg Tray Lids	276	660	
Large Seg Trays	184		
Large Seg Tray Lids	184	440	312
PRTS-6000/4000	184*		
PRTS-5000 Insulated Trays	184		
PPST28/14 Cafeteria Trays			312
PPSTL-28 Lid			312
PPST-1570 Base Tray			312
4" Hotel Pans (12x20x4)			57
PPST-67 Mainline Tray	Use JZDRA-220SP rack with JZDRI-5 Insert		
Sheet Pans	Use JZDRA-220SP rack with JZDRI-4 Insert		

\*with 2" overhang

## COMPONENTS:

### Shelving

- Four shelves
- Eight inserts per shelf, 32 inserts per rack
- Interchangeable inserts – mix and match

### Casters

- Four 6" poly swivel casters with brakes

## INSERTS:

- Inserts made of copolymer material
- Dishwasher safe, temps up to 212° F
- Shatterproof and resists sharpening

### JZDRI-3

- 3" slots (for segregated & insulated trays)
- 23 slots per shelf, 92 per rack

### JZDRI-4

- 1.125" slots (for lids & sheet pans)
- 55 slots per shelf, 220 per rack

### JZDRI-5

- 1.813" slots (for cafeteria trays)
- 39 slots per shelf, 156 per rack